

4X4 – 1500GPM MINI PUMPER #2541



TECHNICAL SPECIFICATIONS

- Ford F750 Crew Cab 4x4 Chassis
- 6.7 L Power Stroke Turbo Diesel 330 HP Engine
- Ford TorqShift HD 10-Speed Transmission
- Heavy Duty Stainless Steel Body with Stainless Steel Subframe
- Stainless Steel Side Control Pump Module w/ Stainless Steel Subframe
- Hale DSD 1500 GPM Pump
- Hale ESP-12PVG Primer
- FRC Pump Boss Pressure Governor Monitoring System
- FRC TankVision Water Tank Level Gauge
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 2½" Gated Intake Left Side
- Two (2) 2½" Discharges, Left Side, One (1) 2½" Discharge Right Side
- Two (2) 2½" Discharges, Rear
- One (1) 3" Discharge Adapted to 5" Storz, Right Side
- FoamPro 1600 Foam System with 20 Gallon Foam Tank
- One (1) 3" Deck Gun Discharge, Dunnage Area
- Two (2) 1½" LA Style Preconnects with Removable Trays
- ROM Roll-Up Doors
- Four (4) Dual Wheel Well Air Bottle Compartments, Two (2) Each Side
- Two (2) Ladder Storage Compartments, Vertical Through the Body One (1) Each Side
- Two (2) Suction Gutters, One (1) Each Side
- 500 Gallon Poly Tank
- One (1) 2½" FirePrograms Tank Fill, Rear
- 12 Volt Electrical System with NFPA Compliant Warning Light Package
- Whelen LED Warning Light Package
- Progressive Dynamics Battery Charger with Viair Compressor
- Kussmaul 20 Amp Super Auto-Eject 120V Shoreline Connection, Left Side
- Federal EQ2B Siren
- Two (2) FRC Spectra Telescopic Lights, One (1) Each Side
- One (1) 10' Attic Ladder, One (1) 12' Roof Ladder with Hooks, One (1) 26' 3-Section Ladder, One (1) 17' Little Giant Ladder, and Two (2) 10' Lengths of 6" Suction Hose
- 9' 11" Overall Height
- 30' 2" Overall Length
- 218" Wheelbase
- 108" Cab to Axle
- 14,000 FAWR
- 26,000 RAWR
- 37,000 GVWR



