

3,000-GALLON TANKER #2561



TECHNICAL SPECIFICATIONS

- Freightliner M2 112 2-Door Tandem Chassis
- 450 HP Cummins L9 Diesel Engine
- Allison 3000 EVS Automatic Transmission
- Two (2) Person Cab
- Heavy-Duty Stainless Steel Body and Subframe
- Stainless-Steel Intermediate Pump Module
- Waterous 1250 gpm PTO Pump
- Trident Air Prime System
- FRC Pump Boss Pressure Governor & Monitoring System
- Two (2) 6" Intakes, One (1) Each Side w/ Akron 7983 Butterfly Valve Left Side
- One (1) 2½" Gated Intake Left Side
- One (1) 2½" FirePrograms Tank Fill, Rear
- Two (2) 2½" Discharges Left Side
- One (1) 2½" Discharge Right Side
- One (1) 3" Discharge Right Side adapted to 5" Storz
- Akron 3423 Deck Gun w/ TFT Extend-A-Gun, Hosebed Dunnage
- Mattydale Preconnect Module, One (1) 1½" | One (1) 2½" | One (1) Deadlay
- 3,000-Gallon Poly Tank
- Two (2) 10' x 6" Hard Suction Gutters, Left Side with Pike Poles and Attic Ladder Bracket
- Ladder Brackets Right Side
- Two (2) 3,000-Gallon Folding Tanks, One Each Side Under Tank T
- Four (4) Folding Steps, Rear
- ROM Satin Finish Roll Up Doors
- One (1) 500# Roll Out Tray L1 Compartment
- Four (4) Walk-Away Air Pack Brackets and Two (2) Extinguisher Mounts R1 Compartment
- Two (2) Dual Bottle Wheel Well Compartments, One (1) Each Side Ahead
- One (1) 10" Newton Stainless-Steel Manual Swivel Dump, Rear
- Progressive Dynamics Battery Charger with Viair Compressor and Kussmaul 120V 20A Super Auto Eject
- Whelen Lightbar and TecNiq Warning Light Package
- Whelen Scene Light Package
- Whelen Electric Siren & 100 W Speaker
- 10' Overall Height
- 32' 10" Overall Length
- 238" Wheelbase
- 172.5" Cab to Axle
- 16,000 FAWR
- 46,000 RAWR
- 62,000 GVWR



