

1500 GPM MINI PUMPER #2538



TECHNICAL SPECIFICATIONS

- Ford F-550 4x4 Super Duty Crew Cab Chassis
- 6.7L 4V OHV V8 Turbo Diesel Engine
- TorqShift 10-Speed Automatic Transmission
- Heavy Duty Stainless Steel Body and Stainless Steel Subframe
- Stainless Steel Side Control Pump Module with Stainless Steel Subframe
- LuVerne Stainless Steel Cab Side Entry Steps
- Go Industries Brush Guard with Hitch and Rear Hitch with Winch Wiring
- Front Hose Well for 100' of 1½" Hose
- Hale DSD 1500 GPM Split Shaft Pump with Hale ESP Priming Pump
- FRC InControl Pressure Governor and FRC TankVision Water Tank Level Gauge
- Two (2) 6" Intakes, One (1) Each Side
- One (1) 5" Rear Intake, Adapted to 6" NSTM
- One (1) 2½" Gated Intake Left Side
- One (1) 2½" Discharge, Each Side and One (1) 3" Discharge, Right Side
- One (1) 3" Deck Gun Discharge with Akron 3433 Hi Riser Monitor
- One (1) 1½" Brush Guard Preconnect
- FoamPro 1600 Foam System with 10 Gallon Integral Foam Tank
- Two (2) 1½" and One (1) 2½" Mattydale Preconnects
- Three (3) Single Wheel Well Air Bottle Compartments
- ROM Satin Finish Roll-Up Doors
- 265-Gallon Poly Tank
- 12 Volt Electrical System with NFPA Compliant Warning Light Package
- Progressive Dynamics Charger with Viair Compressor and Auxiliary Air Tank
- Kussmaul 120V 20A Super Auto Eject, Left Side Above Rear Wheel Well
- Whelen LED Warning and LED Scene Light Package
- Whelen Electronic Siren & 100W Speaker
- Two (2) FRC Telescopic LED Lights, One (1) Each Side Ahead of the Body
- FireTech HiViz 21" LED Brow Light Mounted on the Brush Guard and Brow
- Hard Suction Storage Left Side and Ladder Storage Right Side
- One (1) 10' Attic Ladder, One (1) 12' Roof Ladder with Hooks, One (1) 24' 2-Section Ladder, and Two (2) 10' Lengths of 6" Suction Hose
- 9'-6" Overall Height • 7,500 FAWR
- 28'-3" Overall Length • 14,700 RAWR
- 203.8" Wheelbase • 19,500 GVWR
- 84" Cab to Axle



